10015 FEB 200

Form PTO-1390 (REV. 11-2000)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US)

ATTORNEY'S DOCKET NUMBER
9052-106
U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

	CONCERNING A FILING UNDER 35 U.S.C. 371	10/049779				
INTER	NATIONAL APPLICATION NO. INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED				
	B00/03194 August 18, 2000 OF INVENTION	August 18, 1999				
PROC	ESS FOR SEPARATING METALS					
Robert	CANT(S) FOR DO/EO/US Charles THIED, Justine Elizabeth HATTER, Kenneth Richard SEDDON, Willivid HERDITCH	D. L. ADITALES S. LINEW. DOCUMENT				
	THE THE DELICIT					
Applic	ant herewith submits to the United States Designated/Elected Office (DO/EO/US)	the following items and other information:				
1.	thing under 35 0.3.C. 371.					
2. <u> </u>	This is a SECOND or SUBSEQUENT submission of items concerning a filing					
3.	This is an express request to begin national examination procedures (35 U.S.C.	371(f)). The submission must include				
	items (5), (6), (9) and (21) indicated below.					
4. L	The US has been elected by the expiration of 19 months from the priority date ((Article 31).				
5. 🗵	17 and (35 C.S.C. 371(c)(2))					
	a. is attached hereto (required only if not communicated by the Internal	tional Bureau).				
	b. As been communicated by the International Bureau.					
· □	c. is not required, as the application was filed in the United States Rece					
6.	An English language translation of the International Application as filed (35 U.S.	S.C. 371(c)(2)).				
	a. is attached hereto.					
7.	b. has been previously submitted under 35 U.S.C. 154(d)(4)					
7.	Amendments to the claims of the International Application Under PCT Article 1					
	a. are attached hereto (required only if not communicated by the International Desire house house and its allowed to the communicated by the International Desire house house house house house and the communicated by the International Desire house	ational Bureau).				
	b. have been communicated by the International Bureau.					
	c. have not been made; however, the time limit for making such amended. have not been made and will not be made.	ments has NOT expired				
8. 🗀	and the second made and will not be made.					
o. □ 9. □	An eight or declaration of the investor (a) (25 M.S. C. 274 (a) v. v.)	ticle 19 (35 U.S.C. 371(c)(3)).				
9. 🔲 10. 🗍	An earth or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).					
10.	An English language translation of the annexes of the International Preliminary	Examination Report Under PCT				
	Article 36 (35 U.S.C. 371(c)(5)).					
Itei	ns 11 to 20 below concern document(s) or information included:					
11.	An Information Disclosure Statement under 37 CFR 1.97 and 1.98, Form PTO 1	440 and				
12.						
13. 🖂	An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. A FIRST preliminary amendment.					
14.	A SECOND or SUBSEQUENT preliminary amendment.					
15. 🔲	A substitute specification.					
16. 🔲						
17.	A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C 1 821 - 1.825.					
18. 🔯	A second copy of the published international application under 35 U.S.C. 154(d)(4).					
19. 🔲	A second copy of the English language translation of the international application					
20. 🛛	Other items or information: PCT International Search Report (attached to publish					
	to publish	ned international application)				

U.S.	APPLI	CA10WO/11004	93779	PCT/GB00/03194	LICATION	NO	ATTORNEY DOCKET NO 9052-106	
	21. The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492(a) (1) - (5)).					CALCULATIONS	PTO USE ONLY	
nor	Neither international preliminary examination fee (37 CFR 1 482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1040.00					\$1040.00		
	International preliminary examination fee (37 CFR 1 482) not paid to USPTO but International Search Report prepared by the EPO or IPO					\$890.00		
International preluminary examination fee 37 CFR 1 482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$740.00						\$740.00		
International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4)					\$710.00			
	International preliminary examination fee (37 CFR 1 482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) . \$100.00				\$100.00	\$890 00		
			ENT	ER APPROPRIATE	BASE F	EE AMOUNT =		
		e of \$130.00 for fur earliest claimed pri	mishing the oath o	r declaration later than			\$	
CL	AIM	S	NUMBER FIL	ED NUMBER EX	XTRA	RATE	\$	
Tot	al cla	aims	18 - 20 =	0		x \$18.00	\$	
Ind	epen	dent Claims	1 - 3 =			x \$84.00	\$	
MU	LTI	PLE DEPENDEN	IT CLAIM(S) (i	f applicable)		+ \$280.00	\$	
			TOT	TAL OF ABOVE O	CALC	ULATIONS =	\$	
	App	licant claums small		37 CFR 1.27. The fees				
	redu	iced by 1/2					\$	
				·	S	SUBTOTAL =	\$	
Pro	cessir	ng fee of \$130.00 fo	or furnishing the E	nglish translation later t	than 🔲 🛭	20 🔲 30		
mor	ths f	rom the earliest clai	med priority date	(37 CFR 1.492(f))			\$	
				TOTAL	NATI	ONAL FEE =	\$	
Fee	for R	ecording the enclose	sed assignment (3'	7 CFR 1.21(h)) The as	signmen	t must be		
acco	mpa	nied by an appropri	ate cover sheet (3	7 CFR 3.28, 3 31). \$40	.00 per p	property +	\$	
				TOTAL F	FEES E	ENCLOSED =	\$890 00	
						Amount to be refunded:	\$	
							charged:	\$
a.	\boxtimes	A check in the am	ount of \$890.00 to	cover the above fees is	s enclose	d.		
b. Please charge my Deposit Account No. 50-0220 in the amount of \$ to cover the above fees A duplicate copy of this sheet is enclosed								
c.	\boxtimes							
d.								
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.								
	SEND ALL CORRESPONDENCE TO:							
					ι	Laura M. Kelley, I	Reg No 48,441	
						Date: Feb.	18,2002	
			············		_		CATE OF EXPRESS MAI	LING
		20792				ail Label No. EL 920 posit February 18, 2		
		PATENT TRADEMAR	K OFFICE		I here	eby certify that this co	orrespondence is being depo	
				1	States Post	tal Service "Express Needste indicated above	Mail Post Office to Address and is addressed to: BOX	ee" service under 37 CFR
				P	atents, W	ashington, DC 20231	Attn: DO/PO/US.	
ļ					All	NUN C. , 1	Trucculan	
L					usan E. F	reedman		

Attorney's Docket No. 9052-106

PATENT

IN THE UNITED STATES DESIGNATED OFFICE (DO/US)

In re: Application of Thied et al.

Serial No.: To be Assigned Filed: Concurrently Herewith

For:

PROCESS FOR SEPARATING METALS

February 18, 2002

BOX PCT Commissioner for Patents Washington, DC 20231 Attn: DO/EO/US

PRELIMINARY AMENDMENT

Sir:

Prior to the examination of the above application and calculation of claim fees, please amend the above-identified application as follows. Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The marked-up version of the changes to the claims is captioned "<u>Version With Markings To Show Changes</u> Made."

In the Specification:

On page 1, line 1 after the title of the invention, please insert the following section:

-- CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims priority under 35 U.S.C. § 371 from PCT Application No. PCT/GB00/03194 (published under PCT Article 21(2) in English), filed on August 18, 2000 which claims the benefit of Great Britain Application Serial No. 9919496.1, filed on August 18, 1999, the disclosures of which are incorporated by reference herein in their entireties.--

On page 3, line 10, delete the word "STATEMENTS" and insert --SUMMARY--therefor.

In re: Application of Tried et al.

Serial No.: To be assigned Filed: Concurrently herewith

Page 2 of 7

On page 13, line 1, delete the word "CLAIMS" and insert the following: --WHAT IS CLAIMED IS:--

In the Claims:

Please enter the amended claims as follows:

- 2. (Amended) A method according to claim 1 wherein the ionic liquid comprises a cation component.
- 3. (Amended) A method according to claim 2 wherein the cation component comprises an organic cation.
- 5. (Amended) A method according to claim 1 wherein the anode is selected from a group consisting of halide, nitrate, sulphate, tetrafluoroborate, hexafluorophosphate and tetrachloroaluminate.
- 6. (Amended) A method according to claim 1 wherein the anode comprises trifluoromethanesulfonate bis(trifluoromethanesulfonyl)imide.
- 7. (Amended) A method according to claim 1 wherein the ionic liquid is pre-loaded with metal ions.
- 10. (Amended) A method according to claim 9 wherein the metal chloride comprises AgCl or CdCl₂.
- 12. (Amended) A method according to claim 1 further comprising depositing purified metal at the cathode.
- 13. (Amended) A method according to claim 1 further comprising depositing the metal at the cathode as a compound.

In re: Application of Tried et al.

Serial No.: To be assigned Filed: Concurrently herewith

Page 3 of 7

- 14. (Amended) A method according to claim 1, wherein the composition to be separated is irradiated nuclear fuel.
- 15. (Amended) A method according to claim 1, wherein the metal to be separated comprises uranium.
- 16. (Amended) A method according to claim 1 further comprising purifying the ionic liquid for further use.

Please cancel Claims 17-20.

Please insert the following new Claims 21 and 22:

- 21. (New) A method according to claim 1 wherein the metal to be separated comprises plutonium.
- 22. (New) A method according to claim 3 wherein the organic cation is selected from a group consisting of N-substituted pyridinium, N,N'-disubstituted imidazolium, tetraalkylammonium or tetraalkylphosphonium.

In re: Application of Tried et al.

Serial No.: To be assigned Filed: Concurrently herewith

Page 4 of 7

REMARKS

Applicant respectfully requests consideration of the foregoing amendments. The above claims have been amended to better conform to U.S. practice and to eliminate the multiple dependency of claims.

Please enter this amendment prior to calculating the fee in this case. Applicant respectfully requests substantive examination on the merits.

Respectfully submitted,

Laura M. Kelley

Registration No. 48,441

Correspondence Address:

CERTIFICATE OF EXPRESS MAILING

Express Mail Label No. EL 920740500 US

Date of Deposit: February 18, 2002

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: BOX PCT, Commissioner for Patents; Washington, DC 20231, Attn: DO/EO/US.

Susan E. Freedman

Date of Signature February 18, 2002

In re: Application of Tried et al. Serial No.: To be assigned

Filed: Concurrently herewith

Page 5 of 7

Version With Markings To Show Changes Made

In the Specification:

On page 1, line 1 after the title of the invention, the following section has been added:

-- CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims priority under 35 U.S.C. § 371 from PCT Application No. PCT/GB00/03194 (published under PCT Article 21(2) in English), filed on August 18, 2000 which claims the benefit of Great Britain Application Serial No. 9919496.1, filed on August 18, 1999, the disclosures of which are incorporated by reference herein in their entireties.--

In the Claims:

The claims have been amended as follows:

- 2. (Amended) A method according to claim 1 wherein [the cation component of] the ionic liquid <u>comprises a cation component</u> [is an organic cation].
- 3. (Amended) A method according to claim 2 wherein the <u>cation component</u> <u>comprises an</u> organic cation [is N-substituted pyridinium, N,N'-disubstituted imidazolium, tetraalkylammonium or tetraalkylphosphonium].
- 5. (Amended) A method according to [any of the preceding claims] <u>claim 1</u> wherein the [anion component is] <u>anode is selected from a group consisting of halide, nitrate, sulphate, tetrafluoroborate, hexafluorophosphate [or] and tetrachloroaluminate.</u>
- 6. (Amended) A method according to [any claims 1 to 4] <u>claim 1</u> wherein the [anion component is] <u>anode comprises</u> trifluoromethanesulfonate bis(trifluoromethanesulfonyl)imide.

In re: Application of Tried et al. Serial No.: To be assigned

Filed: Concurrently herewith

Page 6 of 7

7. (Amended) A method according to [any of the preceding claims] <u>claim 1</u> wherein the ionic liquid is pre-loaded with metal ions.

10. (Amended) A method according to claim 9 wherein the metal chloride [is] comprises AgCl or CdCl₂.

12. (Amended) A method according to [any of the preceding claims wherein] <u>claim 1</u> <u>further comprising depositing purified metal [is deposited]</u> at the cathode.

13. (Amended) A method according to [any of the preceding claims wherein] <u>claim 1</u> <u>further comprising depositing</u> the metal [is deposited] at the cathode as a compound.

14. (Amended) A method according to [any of the preceding claims] <u>claim 1</u>, wherein the composition to be separated is irradiated nuclear fuel.

15. (Amended) A method according to [any of the preceding claims] <u>claim 1</u>, wherein the metal to be separated [is] <u>comprises</u> uranium [and/or plutonium].

16. (Amended) A method according to [any of the preceding claims wherein, after use in the method, the ionic liquid is purified for further use] <u>claim 1 further comprising</u> <u>purifying the ionic liquid for further use</u>.

Claims 17-20 have been canceled.

Claims 21 and 22 have been added.

21. (New) A method according to claim 1 wherein the metal to be separated comprises plutonium.

In re: Application of Tried et al. Serial No.: To be assigned Filed: Concurrently herewith Page 7 of 7

22. (New) A method according to claim 3 wherein the organic cation is selected from a group consisting of N-substituted pyridinium, N,N'-disubstituted imidazolium, tetraalkylammonium or tetraalkylphosphonium.

3/pr/2

WO 01/13379

PCT/GB00/03194

PROCESS FOR SEPARATING METALS

FIELD OF THE INVENTION

This invention relates to processes for the separation of metals from compositions containing metals. The invention includes processes for the treatment of spent nuclear fuel forming part of a process for reprocessing, conditioning and/or partitioning nuclear fuels. Reference will be made hereinafter mainly to nuclear fuels but it should be understood that the invention is not restricted to any particular type of material and has application outside the nuclear industry.

10

15

20

25

30

5

BACKGROUND OF THE INVENTION

In the metals recovery and refining industry generally, the type of metal recoverable from a solvent is dependent upon the size of the electrochemical window of the solvent in which the metal is dissolved, and from which purification and recovery is taking place. In aqueous solutions, this is governed by the electrochemical window of water or supporting electrolyte. This limits the recovery, purification and electroplating of metals on to surfaces from aqueous solution to those metals whose electrode reduction potentials are more positive than the cathodic limit of the aqueous solution. In acidic aqueous solution, metal ions would not be recoverable where their electrode reduction potentials are more negative than that of the H₃O⁺ ION. Recovery of metals with electrode reduction potentials more negative than H₃O⁺, means that non-aqueous (aprotic) solvents are required. There are a number of aprotic solvents which are used. There are a number of non-protic solvents which are used. These are often molten salts and, for instance, aluminium is industrially purified electrochemically by electrolysis of Al₂O₃ dissolved in molten cryolite Na₃AlF₆. Other aprotic media include the organic solvents, such as acetonitrile, benzene and toluene.

There exists two well developed processes which use molten salts for the reprocessing of irradiated nuclear fuel. The Argonne National Laboratory electrometallurgical treatment (ANL - EMT) process and the Dimitrovgrad State

Scientific Centre, Research Institute of Atomic Reactors (SSC – RIAR) process both use molten salts at high temperatures (773 and 1000K respectively). The ANL process treats the spent nuclear fuel by a process called electrorefining in which current flow is used to oxidise a uranium anode to form uranium ions in the molten salt electrolyte. At the cathode the uranium is reduced and electrodeposited as uranium metal. The SSC – RIAR process uses chemical oxidants (chlorine and oxygen gases) to react with powdered UO₂ fuel to form higher oxidation state compounds such as UO₂Cl₂ which are soluble in the molten salt. At the cathode the uranium compounds are reduced to UO₂, which forms a dendritic deposit.

10

The disadvantage of these processes is that these molten salts are typically mixtures of salts which are liquid only at high temperatures and this causes inherent disadvantages in a reprocessing plant, in particular, as a result of the challenges posed in the engineering of the process and the materials of construction.

15

20

lonic liquids free of molecular solvents were first disclosed by Hurley and Wier in a series of US patents (24446331, 2446339, 2446350). In general terms an ionic liquid is a salt, a mixture of salts, or a mixture of components which produce a salt or a mixture of salts, which melts below or just above room temperature. (As used herein, the term "salt" means an entity comprising entirely of cationic and anionic species). Such liquids are known as "ionic liquids" although this term is sometimes used for salts which melt at relatively high temperatures. In this specification, the term "ionic liquid" refers to a salt which melts at a temperature of up to 100°C.

25

30

Co-pending patent application PCT/GB99/00246 discloses a method for reprocessing spent nuclear fuel which comprises dissolving the spent fuel or constituent parts of the spent fuel in an ionic liquid to substantially separate fissile material from other components of irradiated fuel. Also disclosed is the subsequent treatment of the resulting ionic liquor, either by solvent extraction or electrochemical treatment to recover the dissolved uranium and plutonium.

Whilst the methods described in PCT/GB99/00246 are suitable for general use and, in particular, for use in nuclear fuel reprocessing, it has previously been thought that an electrorefining process, which avoids the need for an initial chemical dissolution step, requires the use of a high temperature molten salt electrolyte. If fuel is chemically oxidatively dissolved, there is less control over the species which are dissolved during this step. All those species which will be oxidised by the oxidising agent added will enter into the solution. Because the oxidising agents and conditions are aggressive, most species will dissolve except for species such as the noble metals.

10 STATEMENTS OF INVENTION

5

15

20

25

30

According to the present invention there is provided a method for separating a metal from a composition including said metal, the method comprising forming an electrolytic cell having an anode, a cathode and an electrolyte, the anode comprising a composition including said metal and the electrolyte comprising an ionic liquid, applying a sufficient potential difference between the anode and the cathode to cause the metal to transfer from the anode to the cathode and be deposited thereon.

lonic liquids offer the ability to broaden the electrochemical window of the solvent in which the metal is dissolved, and from which purification or recovery is taking place. Ionic liquids have advantages over molten salts. As they operate at closer to ambient temperatures, they are probably less aggressive towards construction components, and engineering and process costs are likely to be less. They also have advantages over organic solvents such as acetonitrile, in being non-volatile, with consequent environmental benefits. Furthermore, metal species are usually more soluble in ionic liquids than in organic solvents.

Ionic liquids can be used to electrodeposit metals which are generally considered to be electropositive, for example, metals whose electrode reduction potentials are more positive than the H₃O⁺ ion. An ionic liquid can be used for this task if there are benefits of using ionic liquids over aqueous based solutions. An example is the

electroplating industry (for instance silver) where there are safety and environmental benefits of using ionic liquids rather than cyanide ion solutions.

Using an electrolytic cell in which the electrolyte is an ionic liquid and the anode is the metal composition to be separated, application of a suitable potential difference results in electrochemical oxidation of the metal at the anode, causing it to enter into the ionic liquid electrolyte medium. The soluble metal species is then electrotransported to the cathode where a reduction process occurs. These results are surprising because, previously, molten salts were the only materials with a sufficiently large electrochemical window for an electrochemical process requiring large potential differences, and the temperature at which the process was performed was dictated by the melting temperature of the salt. Ionic liquids provide large electrochemical windows at ambient temperatures.

5

10

25

30

Preferably the cation component of the ionic liquid is an organic cation, for instance, a nitrogen heterocycle such as N-substituted pyridinium (preferably alkylpyridinium, for instance, N-butylpyridinium), N,N'-disubstituted imidazolium (preferably N,N'-dialkylimidazolium, for instance, l-ethyl-3-methylimidazolium), and substituted ammonium and phosphonium, for instance, tetraalkylammonium (for instance, tetraactylammonium) or tetraalkylphosphonium (for instance, tributyltetradecylphosphonium).

The substituents are preferably hydrocarbyl and more preferably alkyl, which may be branched. The hydrocarbyl (e.g. alkyl) groups usually contain from 1 to 18 carbon atoms and some usually from 1 to 8 carbon atoms.

The cation may therefore preferably be a disubstituted imidazolium ion where the substituent groups take the form C_nH_{2n+1} for $1 \le n \le 8$, and the substituent groups are linear or branched groups. In preferred disubstituted imidazolium ions one substituent has n=1, 2, 3 or 4 (of which methyl is particularly preferred) and the other has n=2, 3, 4, 5, 6, 7 or 8 (of which octyl, hexyl and more particularly butyl are

preferred, linear groups being preferred). Alternatively, the cation might be a substituted tetraalkylammonium or tetraalkylphosphonium ion, where the alkyl groups take the form of C_nH_{2n+1} for $1 \le n \le 6$, and are linear or branched groups. Preferred examples include tetrabutylammonium and tetrabutylphosphonium. However, the alkyl groups are preferably of different lengths resulting in asymmetrical substitution. Alternatively, the cation might be a substituted pyridinium ion, where the substituent group also takes the form C_nH_{2n+1} for $1 \le n \le 8$, and the substituent groups are linear or branched groups; suitable substituents include butyl, 2-(2-methyl)propyl, 2-butyl and octyl but straight chain alkyl, especially butyl, is preferred.

5

10

15

20

25

30

The ionic liquid may be a mixture of two or more ionic liquids, which together provide the desired properties such as, for instance, a lower viscosity. An example is a mixture of disubstituted imidazolium in which the components of the mixture have alkyl groups of different lengths, e.g. a mix of l-octyl-3-methylimidazolium chloride ([emim]Cl) and l-ethyl-3-methylimidazolium chloride ([omim]Cl).

The anion component is likely to be an inorganic species such as halide (for instance, chloride), nitrate, sulphate, tetrafluoroborate, hexafluorophosphate or tetrachloroaluminate, triflate which is trifluoromethanesulfonate (CF₃SO₃), and bistrifylimide which is bis(trifluoromethanesulfonyl)imide ([CF₃SO₂)₂N]).

Preferably the ionic liquid will be pre-loaded with metal ions, in order that the electrorefining process can be initiated. Such pre-loading may be achieved by, for example, the addition to the ionic liquid of a soluble uranium salt or a salt such as cadmium chloride. Addition of a metal salt, such as cadmium chloride, results in the reaction of this metal salt with uranium metal, creating metal ions in the solution.

Pre-loading with uranium ions may also be achieved by displacement of a metal chloride, such as AgCl or Cd Cl₂. Alternatively, pre-loading with uranium ions may be achieved by destructive reduction of the electrolyte. At the anode uranium is

oxidised to a soluble uranium species and, within a cathode compartment separated from the bulk of the solution, the organic cation of the ionic liquid or sacrificial organic reagent added to it, is destroyed.

The process can be applied to a variety of metal fuel feeds. Preferably the metal composition to be treated is irradiated nuclear fuel and the metal to be separated is uranium. Uranium or a uranium compound will be deposited at the cathode in a purified form. By changing the potential at the cathode, or by adding a second cathode to the system, it is possible to achieve separation and deposition of partly purified plutonium.

By contrast with a process involving chemical dissolution, in an electrochemical process there can be much greater selectivity of the species to be dissolved. The potential at the anode can be controlled, such that metals which are more electropositive than uranium, and with larger negative Gibbs free energies associated with the species formed in solution, are the only metals which dissolve at the anode. This is the first separation step, as many of the more noble metals will remain behind in an anodic sludge. The ionic liquid now contains a solution of metal ions including uranium and those of more electropositive species. A suitable potential is applied at the cathode, whereby uranium and metals less electropositive than uranium are electrodeposited. This should only include uranium, as those less electropositive metals have not been anodically dissolved.

DETAILED DESCRIPTION OF THE INVENTION

If oxide fuels are to be treated there will probably be a need for a pre-treatment step, such as that performed in the ANL Lithium reduction process, to reduce the oxide fuel and form a metal feed. The metal fuel may also undergo a decladding process. This could take a number of forms such as mechanical removal or chemical dissolution of the cladding.

15

20

In a preferred embodiment of the invention irradiated nuclear fuel feed in the form of metal is placed within an anode basket. The anode basket is then immersed within an ionic liquid, together with a suitable cathode, such as a stainless steel mandrel. Through the application of a suitable potential difference between the anode and cathode, uranium metal will be electrochemically oxidised at the anode, and enter into the ionic liquid electrolyte medium. The soluble uranium species will then be electro-transported to the cathode, where a reduction process occurs. Contaminants with more positive reduction potentials than uranium will remain unoxidised in the anode basket. Similarly, contaminants with more negative reduction potentials than uranium will remain unreduced in solution.

5

10

15

20

25

30

Electro-reduction of the soluble uranium species should result in the deposition of uranium metal (or a uranium compound) at the cathode. Provided that a suitable oxidising potential is applied at the anode and a suitable reduction potential is applied at the cathode, uranium or a uranium compound will be deposited at the cathode in a purified form.

The ionic liquid contains fission product compounds and compounds of the actinide elements which are oxidised from the cathode with the uranium and must be stripped of these contaminants before its subsequent re-use. This may be achieved by any one or a combination of a number of different routes. Selected fission products and actinides such as plutonium can be electrochemically extracted through the application of a suitable potential using a liquid metal cathode such as a mercury electrode. Alternatively, dissolved plutonium may be co-deposited on the cathode with the uranium, irrespective of whether the metals are deposited in the metallic state (in the (0) oxidation state), as complexes or as oxides. Such co-deposition is useful in the manufacture of mixed oxide fuels.

Selective deposition of a metal from a solution containing its ions is well known in the art and does not require detailed explanation here. However all metal ions in a solution will have different electrode reduction potentials to reduce the ions to a

lower positive valency, or to reduce them to zero valency. Electrode reduction potentials are dependent upon the element, the oxidation state of the ion in the solvent and to the presence of other ions or molecules. If a potential is applied across a solution then all metal ions with a more positive potential will be deposited on the cathode. Metal ions with a more negative potential will remain in solution. Once a particular ion has been removed from the solution, the electrode can be removed and replaced with a new one, biased at a slightly more negative potential, for the deposition of the next metal with a more negative reduction potential. If it is desired to deposit two metals together, then a potential more negative than the reduction potential for both ions is applied.

5

10

15

20

25

30

Certain organic cations are selected for the ionic liquid, to give extremely low reduction potentials. The lower the "cathodic window" of the solvent, the greater the range of species which can be removed from solution by electroreduction. For example, imidazolium cations give at least a 1 volt advantage over aqueous solutions.

Fission products may alternatively or additionally be removed from the ionic liquid by the addition of an organic solvent. Addition of an organic species results in the precipitation of fission product compounds. The precipitate can be filtered from the ionic liquid and calcined to convert to oxide prior to a vitrification step. Cleaned ionic liquid can then be recycled to the electrorefiner.

In order to maximise process rate the electro-refining equipment is engineered to minimise anode to cathode distance and the cathode deposit is removed and collected. The latter step also prevents electrical shorting between the anode and cathode due to the growth of metallic dendrites.

The invention will now be further described with reference to the following examples. In each case the reference electrode was immersed in a 0.1 Molar solution of silver nitrate in [bmim] NO₃, separated from the bulk solution in a glass tube with a porous Vycor tip.

Example 1: anodisation of a uranium electrode in [bmim]NO3 at room temperature

An electrochemical cell was set up with a separated platinum coil counter electrode, a Ag reference electrode, a uranium metal plate working electrode and [bmim]NO₃ (l-butyl-3-methylimidazolium nitrate) as electrolyte. Electrolysis was carried out by applying a potential of +0.6V to the uranium electrode. After the passage of 1000 Coulombs, the uranium electrode was removed and weighed. The weight loss of the uranium (0.78g) indicated that the uranium species required 3.2 equivalents per mole, indicating the production of a U(III) species.

10

15

20

25

5

Example 2: electrorefining uranium in [heim]C1 at 70°C

Due to the viscosity of [heim]C1 1-hexyl-3-ethylimidazohium nitrate chloride, this work was carried out at 70°C. A solution of U(III) was produced in [heim]C1 as by electrolysis of a uranium electrode at +0.3 V. This is anodic dissolution of the uranium metal, as in Example 1. Comparison of the charge passed (1235 Coulombs) with the weight loss of the uranium electrode (1.012 g) gives a charge to mass balance of 3.0 eqv/mol, indicating the production of a U(III) species. The platinum counter electrode used in the preparation of this solution was then replaced with a copper wire immersed in the U(III) solution. Electrolysis was carried out at an applied potential of -1.6 V to the copper cathode; the uranium metal electrode served as the anode. A total of 236 Coulombs was passed during the electrolysis. The weight gain of the cathode electrode was only 18.7 mg compared to the 193 mg weight loss of the uranium anode. This clearly shows that uranium has been electrotransported from the anode to the cathode, the current efficiency being only about 10%. Material which settled on the bottom of the cell indicated that deposited uranium does not adhere well to copper. The charge to mass loss of the uranium electrode (236 C/193 mg = 3.0 eqv/mol) indicated that even while acting as a counter electrode, the species produced through anodisation is still U(III).

Example 3: voltammetry of U(III) in [emim]Cl at 80°C

7.99g [emim] Cl was melted at 80°C. A solution containing 0.03mol L⁻¹ (U(III) was produced by the anodiation of a uranium rod (Q^{γ =}111C) as in Example 1. Cyclic voltammograms were recorded in the resulting solution at a glassy carbon electrode. A typical voltammogram is shown in Figure 1. The oxidation of U(III) to U(IV) occurs at potentials greater than ca. -0.2V versus Ag(I)/Ag. This process is irreversible, as demonstrated by the large difference in the anodic and cathodic potentials (-0.06 and -1.07 V, respectively). The reduction of U(III) to U metal occurs at potentials less than ca. -1.5V.

10

20

25

5

This example thus shows the potential at which uranium (III) is reduced to metal, and shows that uranium can be purified from other metals, such as plutonium, by an electrochemical means.

Example 4: anodiation of Pu(III) in [emim]Cl at 90°C

An electrochemical cell was set up with a separated platinum coil counterelectrode, a Ag reference electrode, and a plutonium metal rod working electrode. Electrolysis was carried out by applying a potential of -1.5V to the plutonium electrode. After the passage of 27.5C. the plutonium electrode was removed and weighed. A direct comparison of the weight loss of the plutonium (80mg) with the charge passed would erroneously indicate that the plutonium species generated was Pu(II). However, it was noted that plutonium metal in contact with the ionic liquid reacts spontaneously; the bright metal quickly forms a dark layer of corrosion products as the metal undergoes oxidation and the ionic liquid cation undergoes reduction. This is most likely because the reduction potential of Pu(III) is more negative than that of the 1-ethyl-3-methylimidazolium cation (ca. -2.2V). Therefore, given the known chemistry of plutonium in chloride media, it is most likely that the species generated during electrolysis is Pu(III); the excess weight loss is due to spontaneous corrosion.

This example shows evidence that plutonium can anodically dissolve into an ionic liquid, and that the oxidation state is probably Pu(III).

The spontaneous corrosion of the plutonium is not necessarily a process issue, as when the basket contents are under electrotransport conditions, electrons are passed round the circuit to the cathode, rather than passing to the cations of the ionic liquid.

5

10

15

20

25

30

Example 5: voltammetry of Pu(III) in [emim]Cl at 90°C

Cyclic voltammograms were recorded at a glassy carbon electrode in the Pu(III) solution produced by anodisation of Pu(III) in [emim]Cl described in Example 4. A typical voltammogram is shown in Figure 2. The oxidation of Pu(III) to Pu(IV) occurs at potentials greater than ca. -0.2V. The Pu(IV)/Pu(III) redox couple is quasi-reversible with $\Delta E_p \approx 90 \text{mV}$ ($E_p^a = -0.15 \text{V}$, $E_p^c = -0.24 \text{V}$). From the voltammogram, it is clear that reduction of Pu(III) to generate the metal does not occur at potentials greater than -2.2 V, the cathodic limit of the ionic liquid below which potential the cation is reduced. A comparison of the potential windows of [bmim] [NO₃], [emim]Cl and LiCl-KCl eutectic is shown in Figure 3, which also graphically displays the potentials of various redox couples of plutonium and uranium in [emim]Cl at 90°C from Example 3 and Example 5. It should be clear from this graphic that the electrodeposition of uranium without the simultaneous deposition of plutonium is possible in the [emim]Cl ionic liquid at 90°C, allowing separation of uranium from plutonium.

This graphic shows that the electrochemical window of [emim]Cl at 90° is sufficiently wide that the reduction of U(III) to uranium metal can be performed within the ionic liquid, but is insufficiently wide for this to be the case with plutonium. Hence purification of uranium from plutonium is possible.

Use of a liquid metal electrode, such as mercury, may shift the electrode reduction potential of plutonium, so that it can too be electrodeposited at the liquid cathode. As an alternative, a different ionic liquid may be used, specifically one which has a wider electrochemical window, for instance, a tetraalkylammonium ionic liquid.

Example 6: precipitation of fission products from [hmim]Cl using an organic solvent Europium(III) chloride (EuCl₃) was used to simulate fission products dissolved in an ionic liquid. 4.66g [hmim]Cl and 1.05g EuCl₃ were dissolved in 20cm⁻³ dry acetonitrile. This solution was heated to 70°C under reflux in a dry dinitrogen atmosphere for 3 hours and allowed to cool. After approximately 30 minutes in a refrigerator, fine white crystals had precipitated. 1.81g of precipitate were collected. The results of elemental analysis of the crystals were 41.04% carbon, 6.86% hydrogen, and 9.22% nitrogen. The theoretical composition of the complex [hmim]₃[EuCl₆] (C₃₀Cl₆EuH₅₇N₆, RAM = 866.50 g mol⁻¹) is 41.58% carbon, 6.63% hydrogen and 9.70% nitrogen which suggests that this is the identity of the precipitate.

5

10

This Example shows that fission products dissolved within an ionic liquid can be recovered by the addition of an organic solvent.

CLAIMS

- 1. A method for separating a metal from a composition including said metal, the method comprising forming an electrolytic cell having an anode, a cathode and an electrolyte, the anode comprising a composition including said metal and the electrolyte comprising an ionic liquid, applying a sufficient potential difference between the anode and the cathode to cause the metal to transfer from the anode to the cathode and be deposited thereon.
- A method according to claim 1 wherein the cation component of the ionic liquid
 is an organic cation.
 - 3. A method according to claim 2 wherein the organic cation is N-substituted pyridinium, N,N'-disubstituted imidazolium, tetraalkylammonium or tetraalkylphosphonium.

15

5

- 4. A method according to claim 3 wherein the organic cation includes alkyl groups which are linear or branched and not all of the same chain length.
- A method according to any of the preceding claims wherein the anion component
 is halide, nitrate, sulphate, tetrafluoroborate, hexafluorophosphate or tetrachloroaluminate.
 - 6. A method according to any claims 1 to 4 wherein the anion component is trifluoromethanesulfonate bis(trifluoromethanesulfonyl)imide.

25

- A method according to any of the preceding claims wherein the ionic liquid is preloaded with metal ions.
- 8. A method according to claim 7 wherein the ionic liquid is pre-loaded with metal30 ions by the addition of a soluble uranium salt.

ART 34 AMOF

15

20

30

- 9. A method according to claim 7 wherein the ionic liquid is pre-loaded with uranium ions by displacement of a metal chloride.
- 5 10. A method according to claim 9 wherein the metal chloride is AgCl or CdCl₂.
 - 11. A method according to claim 7 wherein the ionic liquid is pre-loaded with uranium ions by destructive reduction of the electrolyte.
- 10 12. A method according to any of the preceding claims wherein purified metal is deposited at the cathode.
 - 13. A method according to any of the preceding claims wherein the metal is deposited at the cathode as a compound.

14. A method according to any of the preceding claims wherein the composition to be separated is irradiated nuclear fuel.

15. A method according to any of the preceding claims wherein the metal to be separated is uranium and/or plutonium.

- 16. A method according to any of the preceding claims wherein, after use in the method, the ionic liquid is purified for further use.
- 25 17. A process for the reprocessing of spent nuclear fuel, the process including a method of any preceding claim.
 - 18. Use of an ionic liquid in the electrorefining of a composition to separate a metal therefrom.
 - 19. Use according to claim 18 wherein the composition is spent nuclear fuel.

14



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 22 February 2001 (22.02.2001)

PCT

(10) International Publication Number WO 01/13379 A1

(51) International Patent Classification7: G21C 19/48, C25C 1/22

- (21) International Application Number: PCT/GB00/03194
- (22) International Filing Date: 18 August 2000 (18.08.2000)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 9919496.1

18 August 1999 (18.08.1999) GB

- (71) Applicant (for all designated States except US): BRITISH NUCLEAR FUELS PLC [GB/GB]; Risley, Warrington, Cheshire WA3 6AS (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): THIED, Robert, Charles [GB/GB]; British Nuclear Fuels Plc.-Research & Technology, Sellafield Works, Seascale, Cumbria CA20 IPG (GB). HATTER, Justine, Elisabeth [GB/GB]; British Nuclear Fuels PLC, Risley, Warrington, Cheshire WA3 6AS (GB). SEDDON, Kenneth, Richard [GB/GB]; Questor Centre, Queens University, David Keir Building, Stanmillis Road, Belfast BT9 5AG (GB). PITNER, William, Robert [GB/GB]; Questor Centre, Queens University, David Keir Building, Stanmillis Road, Belfast

BT9 5AG (GB). ROONEY, David, William [GB/GB], Questor Centre, Queens University, David Keir Building, Stanmillis Road, Belfast BT9 5AG (GB). HEBDITCH, David [GB/GB]; BNFL Magnox Generation, Berkeley, Gloucestershire GL13 9PB (GB).

- (74) Agent: HARRISON GODDARD FOOTE; Tower House, Merrion Way, Leeds LS2 8PA (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

With international search report.


For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette

(54) Title: PROCESS FOR SEPARATING METALS


(57) Abstract: A method for separating a metal from a composition including the metal involves forming an electrolytic cell in which the anode comprises a composition including the metal. The electrolyte is an ionic liquid. A sufficient potential difference is applied between the anode and the cathode to cause the metal to transfer from the anode to the cathode and to be deposited thereon.

WO 01/13379

PCT/GB00/03194




1 / 3
SUBSTITUTE SHEET (RULE 26)



2 / 3

WO 01/13379

PCT/GB00/03194



3 / 3

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION Attorney Docket No. 9052-106

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled ,

is claimed and for which a patent is sought on the invention entitled,
the specification of which
is attached hereto
OR .
was filed on February 18, 2002 as United States Application No. or PCT International Application Number (10/049,779) and was amended on (if applicable). I hereby authorize and request Myers, Bigel, Sibley & Sajovec, P.A. to insert above in parenthesis the U.S. application number assigned to the application which claims priority in International Application No. PCT/GB00/03194 when known.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37 Code of Federal Regulations, §1.56, including material information that became available between the filing date of the prior application and the National or PCT International filing date of the continuation-in-part application, if applicable.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate, or of any PCT International application having a filing date before that of the application on which priority is claimed.

DCT/CD00/02104			
PCT/GB00/03194	PCT	August 18, 2000	Yes No
Number	Country	MM/DD/YYYY Filed	Priority Claimed
9919496.1	Great Britian	August 18, 1999	⊠ Yes □ No
Number	Country	MM/DD/YYYY Filed	Priority Claimed

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)
Application Number(s)	Filing Date (MM/DD/YYYY)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or § 365(c) of any PCT international application designating the United States of America, listed below.

Appln. Serial No.	Filing Date	Status Patented/Pending/Abandoned
Appln. Serial No.	Filing Date	Status Patented/Pending/Abandoned
		ì
Appin. Serial No.	Filing Date	Status Patented/Pending/Abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following registered attorney(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. I also appoint the following registered attorney(s) to represent me before all competent International Authorities in connection with any and all international applications filed by me with an appropriate receiving office claiming priority to the U.S. application. I also appoint the following registered attorney(s) to make or receive payment on my behalf in connection with the filing of such international applications.

Customer Number:



PATENT TRADEMARK OFFICE

Send correspondence to:

Citizenship:

Mailing Address:

Customer Number:

20792

Direct telephone calls to: (919) 854-1400 Facsimile: (919) 854-1401 Full name of (first/sole) inventor: I-IIInventor's - Mela Tind Date: 23nd April 2002.

= CUMBRIA, GREAT BRITAIN (D) Signature: Residence: SEASCALE, CUMBRIA, Citizenship: BRITISH. Mailing Address: SELLAFIELD Full name of second inventor: ` Justine Elizabeth HATTER Inventor's ____ Date: Signature: Residence:

Page 3 of 5

Customer Number:

Send correspondence to:

Customer Number:

Direct telephone calls to:

(919) 854-1400

Facsimile:

(919) 854-1401

Full name of (first/sole) inventor:

Robert Charles THIED

Inventor's

Signature:

Date:

Residence:

Citizenship:

Mailing Address:

Full name of second inventor.

Justine Elizabeth HATTER

Inventor's

Signature: Justine Elizabeth Hatter Date: 30/4/2002

Residence: CHESHIRE, GREAT BRITAIN

Citizenship: BRITISH

Mailing Address: RISLEY, WARRINGTON, CHESHIRE, WA3 6AS, GREAT BRITAIN

Page 3 of 5

3-00
Full name of third inventor: Kenneth Richard SEDDON
Inventor's Signature: Date:
Residence: UK
Citizenship: BRITISH
Mailing Address: SCHOOL OF CHEMISTRY, QUEEN'S UNIVERSITY BAND KEIR BUILDING STRANHILLS ROAD BELFAST BT9 SAG, N. IRELAND (MS
Full name of fourth inventor: 4-0 William Robert PITNER
Inventor's Signature: Date: 22/64/62
Residence: UK
Citizenship: USA
Mailing Address: School of Chemistry Queen's University
Full name of fifth inventor: 50 David William ROONEY
Inventor's Signature: Date: 7/5/02
Residence: UK
Citizenship: IRISH
Mailing Address: SCHOOL OF CHEMICAL ENGINEERING
QUEENS UNIVERSITY SECTAD.
BECFAUT BT9 CACChS

Full name of sixth inventor: David HEBDITCH

Inventor's

Signature: Description Date: June 11, 2002

Residence: GREENCEIDE BOADA

GREENSIDE, BRADLEY GREEN, WOTTON-UNDER-EDGE, GLOVE ESTERSHIRE, ENGLAND GLIZ 7PE

Citizenship: BRITISH

Mailing Address:

BNFL RUTHERFORD R201 RISLBY

WARRINGTON

WA3 GAS